

Tender for Supplying Hospital Furniture
At
All India Institute of Medical Sciences,
Rishikesh
Date: 24-04-2017



Date & Time of Pre bid meeting 04-05-2017 at 03.00 PM
Last Date & time of submission of bid 17-05-2017 at 03.00 PM
Date & time of Opening of bid 17-05-2017 at 03.00 PM

All India Institute of Medical Sciences, Rishikesh
Virbhadr Marg, Rishikesh-249201, Uttarakhand,
Phone: 0135-2462915

Email: tenderaiimsrishikesh@gmail.com,
[Web-site www.aiimsrishikesh.edu.in](http://www.aiimsrishikesh.edu.in)

Sign of bidder

Chapter I- Instruction to bidders

Notice Inviting Tender for Supplying Hospital Furniture

1. The AIIMS, Rishikesh, Uttarakhand, invites sealed tender under two-bid system from manufacture and their authorized dealers/distributor for supply of the "Hospital Furniture". You are requested to quote your best offer along with the complete details of specifications, terms & conditions.
2. The interested manufacture and their authorized dealers/distributors are required to submit the technical and financial bid separately. The bids in Sealed Cover-1 containing "Technical Bid" and Sealed Cover-II containing "Financial Bid" should be placed in a third sealed cover super scribed Tender for supply of the "**Hospital Furniture**". Tender documents containing detailed information/terms and conditions for the purpose can either be obtained from the Administrative Office, AIIMS, Rishikesh from **24-04-2017 to 17-05-2017** between 10.00 AM to 02.00 PM on non-refundable payment of Rs. 1145/- (Rupees one thousand one hundred forty five only) or can be download from website www.aiimsrishikesh.edu.in. Those who download the tender document from website should enclosed the DD for Rs. 1145/- (Rupees one thousand one hundred forty-five only) (non-refundable) in favor of AIIMS Rishikesh payable at Rishikesh, which shall be of not later from 16-05-2017 along with their bid. The bid security (EMD) for Hospital Furniture as given in table-1 below tender documents should be paid in the form of Demand Draft/FD/TD/CD in favour of "AIIMS, Rishikesh" payable at Rishikesh and will be placed in cover-1 with technical bid. The Tender Documents are not transferable.
3. Sealed Tender duly super scribed "Tender for Hospital Furniture" addressed to the undersigned may be sent by post so as to reach by 3.00 P.M. on or before 17-05-2017 or dropped in the Tender Box kept at Tender Office of AIIMS, Rishikesh not later than 3.00 P.M. of 17-05-2017. Tender received after stipulated date/time shall not be entertained under any circumstances. The Tender will be opened on the same day at 03.00 P.M. at Tender Office of AIIMS, Rishikesh in the presence of the tenderers or their representatives who may like to be present.
4. The pre bid conference would be held on **04-05-2017 at 03.00 PM** in the Tender Opening Room, AIIMS, Rishikesh. All firm's representative who are attending the pre bid meeting, shall produce an authorization letter from their firm on the firm's letter head. They are required to put their query in writing before the committee.
5. Any future clarification and/or corrigendum(s) shall be communicated through Administrative Officer on the AIIMS, Rishikesh website www.aiimsrishikesh.edu.in.
6. Bidder should necessary enclose a covering letter mentioning a summary of applied document with proper numbering & mentioning the name of item & its brand & model No. Secondly bid should also attach a compliance sheet as per specification mentioning they are complying to all specification or have any variation.

Administrative officer
AIIMS Rishikesh
Tel No. 0135-2462915.

Sign of bidder

Chapter-II- Conditions of Contract
General Terms and Conditions

Subject: - Notice Inviting Tender for Supplying Hospital Furniture for All India Institute of Medical Sciences, Rishikesh

1. Earnest Money :

Earnest money by means of a demand draft/FD/TD/CD those firm quote for all items will have to submit EMD of Rs 4,05,000/- (Rupees four lakh five thousand only) and who quote for individual items can submit partly EMD mentioned against each item in favour of AIIMS Rishikesh, payable at Rishikesh may be enclosed with the quotation (Technical Bid). It is also clarified that the bid received without earnest money will be summarily rejected.

- a) No request for transfer of any pervious deposit of earnest money or security deposit or payment of any pending bill held by the ministry in respect of any previous work will be entertained.
- b) Tenderer shall not be permitted to withdraw his offer or modify the terms and conditions thereof. In case the tenderer fails to observe and comply with stipulations made herein or backs out after quoting the rates, the aforesaid amount of earnest money will be forfeited.
- c) Bidders are not allowed to submit more than one bid for the same/similar tendered item else all his bids shall be cancelled thereby making him disqualified in addition to the forfeiture of the EMD.
- d) Tenders without Earnest Money or Tender cost will be summarily rejected.
- e) No claim shall lie against the AIIMS in respect of erosion in the value or interest on the amount of EMD.
- f) Unsuccessful tenderers earnest money will be returned to them without any interest after the expiration of 30 days from the conclusion of the Contract.

2. Preparation and Submission of Tender:

The tender should be submitted in two parts i.e. Technical Bid and Financial Bid. The Technical Bid and the Financial Bid should be sealed by the bidder in two separate covers "**Technical Bid for Tender for Supply of Furniture** "and "**Financial Bid for Tender for Supply of Furniture** ". Both Sealed Envelopes should be kept in a main/ bigger envelope super scribed as "**Tender for Supply of Furniture** "

3. Signing & sealing of Tender:

The individual signing the tender or other documents connected with contract must specify whether he sign as:

- (a) A sole proprietor of the concern or constituted attorney of such sole proprietor;
- (b) A partner of the firm, if it is a partnership firm in which case he must have

Sign of bidder

Re-Tender Enquiry. No.24/Furniture/213/2017-RISH(ADMN)

authority to execute the contracts on behalf of the firm and to refer to arbitration disputes concerning the business of the partnership either by virtue of the partnership agreement or by a power of attorney duly executed by the partners of the firm.

- (c) Director or a principal officer duly authorized by the Board of Directors of the Company, if it is a company.

N.B.

(1) In case of partnership firms, a copy of the partnership agreement, or general power of attorney duly attested by a Notary Public, should be furnished on stamped paper duly sworn or affirmed by all the partners admitting execution of the partnership agreement or the general power of attorney. The attested copy of the certificate of registration of firm should also be enclosed along with the tender.

(2) In the case of partnerships firm, where no authority to refer disputes concerning the business of partnership firm has been conferred on any partner, the tender and all other related document must be signed by all partners of the firm.

(3) A person signing the tender form or any document forming part of the tender on behalf of another person should have an authority to bind such other person and if, on enquiry it appears that the person so signing had no authority to do so, AIIMS, Rishikesh may without prejudice, cancel the contract and hold the signatory liable for all costs, consequences and damages under the civil and criminal remedies available.

(4) **The tenderer should sign and affix his firm's stamp at each page of the tender and all its annexure as the acceptance of the offer made by tenderer will be deemed as a contract and no separate formal contract will be drawn.** NO PAGE SHOULD BE REMOVED/ DETACHED FROM THIS NOTICE INVITING TENDER.

(5) The tender shall not contain any erasure or overwriting except as necessary to correct any error made by the tenderer.

4. **Opening of Tender:**

AIIMS, Rishikesh will open the tenders at the specified date & time at tender opening room. The tenderer is at liberty to present either him or authorize not more than one representative to be present at the opening of the tender. The representative present at the opening of the tender on behalf of the tenderer should bring with him a letter of authority from the tenderer and proof of identification.

Financial bids will be open to only those bidders who submitted their sample by or before opening of financial bid and whose sample is passed by a technical committee after technical evaluation.

Sign of bidder

5. **Validity of the bids:**

The bids shall be valid for a period of six months from the date of award of work.

6. **Right of acceptance:**

AIIMS, Rishikesh reserve the right to accept or reject any or all tenders /quotations without assigning any reason there of and without incurring any liability what so ever to the effected tenderer and also does not bind itself to accept the lowest quotation or any tender.

Any failure on the part of the tenderer to observe the prescribed procedure and any attempt to canvass for the work will prejudice the tenderers quotation or any tender.

7. **Communication of Acceptance**

AIIMS, Rishikesh will notify the successful tenderer in writing by registered/speed post/Fax etc. that its tender for goods & services, which have been selected by the purchaser has been accepted.

8. **Right of Acceptance**

AIIMS, Rishikesh reserves all right to reject any tender including of those tenderers who fails to comply with the instructions without assigning any reason whatsoever and does not bind itself to accept the lowest or any specific tender. The decision of this Institute in this regard will be final and binding. Any failure on the part of the contractor to observe the prescribed procedure and any attempt to canvass the work prejudice the contractor's quotation.

9. **Performance Security:**

The successful tenderer will be required to furnish a Performance Security Deposit of 10% of tender amount in the form of BG/FD/TD/CD from any Nationalized/Schedule Bank duly pledged in the name of the All India Institute of Medical Sciences, Rishikesh, payable at Rishikesh. The performa for performance security deposit is attached with the tender document.

The security deposit can be forfeited by order of this Institute in the event of any breach or negligence or non-observance of any condition of contract or for unsatisfactory performance or non-observance of any condition of the contract. Security will be discharged after completion of tendereres performance obligations (including Comprehensive maintenance contract period) under the contract.

10. **Corrupt Practices:**

The tenderer is required to observe the highest standard of ethics during procurement & execution of contract. AIIMS Rishikesh have right to reject proposal for

Sign of bidder

Re-Tender Enquiry. No.24/Furniture/213/2017-RISH(ADMN)

award if it finds that the tenderer has engaged in corrupt or fraudulent practices in competing for the contract in question. An undertaking on this behalf shall be given in the format enclosed with this tender document.

11. Delivery & Installation:

The Furniture shall be delivered within 30 days of issue of supply order. Satisfactory installation / commissioning and handover of the furniture will be completed within two weeks from the date of receipt of the furniture at the AIIMS, Rishikesh premises.

12. Inspection, Testing and Quality control

- (i) The purchaser or its nominal representative will inspect and test the ordered goods and the related services to confirm their conformity to the contract specification and other quality control details incorporated.
- (ii) The Purchaser reserves the right for stage inspection during manufacturing process, pre-dispatch inspection or post-delivery inspection. The Purchaser as deemed fit shall resort to all these inspections or may waive off any of the inspection.
- (iii) Stage Inspection: The Supplier shall offer semi-finished product without paint for stage inspection supported with invoice & test report of major raw material as per relevant specification standards.
- (iv) Before resorting to Bulk Manufacture, the supplier shall offer/send the prototype/actual finished sample for approval by the Inspector. The approval of Samples shall be in respect of workmanship and finishing and shall be without prejudice to the rights of purchaser/user to get random testing of items during pre-dispatch inspection or from the actual lot offered. In the event of the failure of the supplier to deliver the sample by the date specified in the contract or any other date agreed by the purchaser or in the event of rejection of the sample second time, the purchaser shall be entitled to cancel the contract and purchase the stores at the risk and cost of the supplier.
- (v) The Inspector shall have full and free access at any time during the execution of the contract to the supplier's work for satisfying himself that the goods are being manufactured in accordance with the specification mentioned in the Contract, and he may require the Supplier to make arrangements of inspection of the goods or any part thereof or any material at his premises or at any other place specified by the Inspector and if the Supplier has been permitted to employ the services of a sub-inspection of the goods after they have been inspected by the Inspector for the purpose aforesaid. The decision of the purchaser/ inspection authority in this regard shall be final and binding on the Supplier. All terms and condition of the contract as they apply to the inspection shall

Sign of bidder

Re-Tender Enquiry. No.24/Furniture/213/2017-RISH(ADMN)

also apply to the re-inspection.

- (vi) The Supplier shall provide, without any extra charge, all material, tools, labour and assistance of every kind which the Inspector may demand of him for any test, and examination, which he shall require to be made on the Supplier's premises and the Supplier shall bear and pay all costs attendant thereon. If the Supplier fails to comply with condition aforesaid, the Inspector shall, in his sole judgement, be entitled to remove for test and examination all or any of the goods manufactured by the Supplier to any premises other than his (Supplier's) and in all such cases the Supplier's shall bear the cost of transport/and carrying out such tests elsewhere. A certificate in writing of the Inspector, that the Supplier has failed to provide the facilities and the means for test and examination, shall be final.
- (vii) The Supplier shall also provide and deliver for test, free of charge, at such place other than his premises as the Inspector may specify such material or goods as he may require for tests for which Supplier does not have the Facilities or special/independent tests. The Inspector shall have the right to put all the goods or materials forming part of the same or any part thereof to such tests as he may think fit and proper. The Supplier shall not be entitled to object on any ground whatsoever to the method of testing adopted by the Inspector. Goods accepted by the purchase/AIIMS, Rishikesh and/or its inspector at initial inspection and in final inspection in terms of the contract shall in no way dilute purchaser's (AIIMS, Rishikesh) right to reject the same later.
- (viii) The Purchaser's Inspector reserves the right to draw samples through random sampling method after receiving the finished goods at destination. All the supplies shall be accompanied with the Manufacturer's certificate that the material conforms to the specifications.

Further more if, on the goods being rejected by the Inspector or AIIMS, Rishikesh at the destination, the Supplier fails to make satisfactory supply within the stipulated period of delivery the Purchaser shall be at liberty to: -

- (a) Require the Supplier to replace the rejected goods forthwith but in any event not later than a period of 10 days from the date of rejection and the Supplier shall bear all cost of such replacement, including freight, if any, on such replacing and replaced goods but without being entitled to any extra payment on that or any other account.
- (b) Purchase or authorize the purchase of quantity of the goods rejected or goods of a similar description when goods exactly complying with particulars are not available in the opinion of the Purchaser, which shall be final, readily available without notice to the supplier at his risk and cost and without affecting the Supplier's liability as regards the supply of any further instalment due under the contract, or
- (c) Cancel the contract and purchase or authorised the purchase of the goods

Sign of bidder

Re-Tender Enquiry. No.24/Furniture/213/2017-RISH(ADMN)

or goods of a similar description (when goods complying with particulars are not in the opening of the Purchase, which shall be final, readily available) at the risk and cost of the Supplier.

- (d) The Inspector shall have the power: -
- (i) Before any goods or part thereof are submitted for inspection to certify that they cannot be in accordance with the contract owing to the adoption of any unsatisfactory method of manufacture.
 - (ii) To reject any goods submitted as not being accordance with particulars.
 - (iii) To reject the whole of the instalment tendered for inspection, if after inspection of such portion thereof as he may in his discretion think fit, he is satisfied that the same is unsatisfactory.
 - (iv) To demand all cost incurred in the inspection and/or test. Cost of test shall be assessed at the rate charged by the Laboratory to private persons for similar work However if goods are accepted all cost incurred shall be borne by the Purchaser.

Inspector's decision as regards the rejection shall be final and binding on the Supplier

13. Guarantee / Warranty:

- (i) The on-site replacement warrant shall remain for a period of 36 Month from the date of recording of acceptance of goods at site.
- (ii) During warranty period, the supplier is required to visit AIIMS, Rishikesh's site at least once in 4 months commencing from the date of delivery of the goods for preventive maintenance of the goods.
- (iii) If the supplier having been notified, fails to respond to take action to replace the defect(s) within 10 days the purchaser may proceed to take remedial action(s) as deemed fit, at the suppliers risk & cost.
- (iv) In the event of any correction of defects or replacement of defective material during the warranty period, the warranty for the corrected or replaced material shall be extended to a further period of 36 months.
- (v) Free maintenance services shall be provided by the supplier during warranty period.

14. Liquidated Damages

The time for the date of delivery/ dispatch stipulated in supply order shall be deemed to be essence of the contract and if the supplier fails to deliver or dispatch any consignment within the period prescribed for such delivery or dispatch in the supply

Sign of bidder

order, liquidated damages may be deducted from the bill @ 0.5% per week subject to maximum of 10% of the value of the delayed goods or services under the contract. The competent authority of the institute may also cancel the supply. In such a case, bid security of the supplier shall stand forfeited.

15. FORCE MAJEURE :

If, at any time during the subsistence of this contract, the performance in whole or in part by either party of any obligation under this contract is prevented or delayed by reasons of any war or hostility, act of public enemy, civil commotion, sabotage, fire, floods, explosion, epidemics, quarantine restriction, strikers lockout or act of God (hereinafter referred to as events) provided notice of happening of any such eventuality is given by party to other within 21 days from the date of occurrence thereof, neither party shall by reason of such event be entitled to terminate this contract nor shall either party have any claim for damages against other in respect of such non-performance or delay in performance, and deliveries have been so resumed or not shall be final and conclusive.

Further, that if the performance in whole or in part of any obligation under this contract is prevented or delayed by reason of any such event for a period exceeding 60 days, AIIMS, Rishikesh party may, at least option to terminate the contract.

16. Insolvency etc.:

In the event of the firm being adjudged insolvent or having a receiver appointed for it by a court or any other order under the Insolvency Act made against them or in the case of a company the passing any resolution or making of any order for winding up, whether voluntary or otherwise, or in the event of the firm failing to comply with any of the conditions herein specified AIIMS, Rishikesh shall have the power to terminate the contract by giving written notice to the supplier. Such a termination shall not prejudice any right or remedy which has accrued or will accrue thereafter to the purchaser.

17. Breach of Terms and Conditions:

In case of breach of any terms and conditions as mentioned above, the Competent Authority, will have the right to cancel the work order/ job without assigning any reason thereof and nothing will be payable by AIIMS, Rishikesh. In that event the security deposit shall also stands forfeited. Non-performance of any of the contract provisions will disqualify a firm to participate in tenders issued by AIIMS Rishikesh for the next five years. In the event of making alternative purchase, the supplier will be imposed penalty apart from forfeiture of security deposit.

18. Subletting of Work:

The firm shall not assign or sublet the work/job or any part of it to any other person or party without having first obtained permission in writing of AIIMS, Rishikesh, which will be at liberty to refuse if thinks fit. The tender is not transferable. Only one tender shall be submitted by one tenderer.

Sign of bidder

19. **Right to call upon information regarding status of work:**

The AIIMS, Rishikesh will have the right to call upon information regarding status of work/ job at any point of time.

20. **Terms of payment:**

100% payment shall be made receipt and acceptance of material by consignee after the successful installation of the ordered goods against the submission of invoices in triplicate along with inspection report original copy of work order/supply order and receipt voucher of central stores.

21. **Patent Rights:**

In the event of any claim asserted by a third party of infringement of copyright, patent, trademark or design right arising out of use of the goods or any part thereof, the supplier shall extinguish such claims. The supplier shall be responsible for the companies.

22. **Arbitration:**

In case of Dispute or difference between the parties relating to any matter arising out of this contract, the same shall be settled in accordance with the arbitration & conciliation act, 1996 by sole arbitrator. The sole arbitrator shall be appointed by agreement between the parties. Arbitration proceedings shall be held at AIIMS, Rishikesh, Rishikesh/Dehradun as agreed between the parties & the language of arbitration proceedings & that of all documents & communications between the parties shall be either Hindi or English.

The decision of arbitrator shall be final & binding upon both the parties. The cost & expenses of the proceedings will be paid as determined by the arbitrator. However, the expenses incurred by each party in connection with the preparation, presentation etc, of its proceedings shall be borne by party itself.

23. **Saving Clause:**

No suit, prosecution of legal proceedings shall lie against AIIMS, Rishikesh or any person for anything done in good faith in pursuance of tender.

24. **Legal Jurisdiction:**

The agreement shall be deemed to have been concluded in Rishikesh, Uttarakhand and all obligations hereunder shall be deemed to be located at Rishikesh/Dehradun, Uttarakhand and Court within Rishikesh/Dehradun, Uttarakhand will have Jurisdiction to the exclusion of other courts.

Sign of bidder

25. **Applicable Law:**

The contract shall be interpreted in accordance with the laws of union of India.

26. At the time of awarding the contract, the purchaser reserves the right to increase or decrease up to twenty-five (25%), the quantity of goods and services mentioned in the schedule(s) in the "Schedule of Requirements" (round of to nextwhole number) without any change in the unit price and other terms & conditions quoted by the bidder.

27. If the quantity has not been increased at the time of the awarding the contract the purchaser reserves the right to increase up to twenty-five (25%), the quantity of goods and services mentioned in the contract (rounded of to next whole number) without any change in the unit price and other terms & conditions mentioned in the contract, during the currency of the contract after one year from the date of Purchase Order.

I/We hereby accept the terms and conditions given in the tender.

(Signature & Stamp of the bidder)

Note: Please sign each page of document including terms & conditions & tender.

Sign of bidder

UNDERTAKING ON FRAUD & CORRUPTION (FOR BIDDER)

We..... do hereby undertake that, in competing for (and if the award is made to us, in excluding) the subject contract for supply of Hospital Furniture/Equipments under tender reference No..... We shall strictly observe the terms & conditions against fraud, corruption & mal practices in force in the country.

(Dated Signature of the Tenderer with stamp of firm)

Date:

Place:

Sign of bidder

Table -I

Items for the AIIMS Rishikesh
Details of items & their tentative quantity and EMD

(To be submitted on the letterhead of the company / firm)

Sr.No	Name of Item	Requirement	EMD	Total EMD
1	2	3	4	5
1	Crash Cart	10	₹ 15,000.00	₹ 4,05,000.00
2	Bed Side Locker	188	₹ 25,000.00	
3	Bed Side Screen (Ward Screen) Stainless Steel with single curtain, three section	80	₹ 15,000.00	
4	Fowler Bed, four section with mattresses and pillow	200	₹ 1,60,000.00	
5	Dressing Trolley	15	₹ 3500.00	
6	Over bed trolley (Food Trolley)	200	₹ 50,000.00	
7	Stainless Steel Operation Instruments Trolley (Without Bucket Ring)	15	₹ 4,000.00	
8	Medicine Trolley	25	₹ 12,000.00	
9	Patient Examination Couch	8	₹ 6,000.00	
10	Examination Couch (Low Height)	4	₹ 20,000.00	
11	Stool SS, Round & Revolving top, Adjustable for heights	200	₹ 20,000.00	
12	Solid Linen Trolley	25	₹ 20,000.00	
13	Wheel Chair (SS)	15	₹ 12,000.00	
14	Single Foot Step	30	₹ 1,000.00	
15	Foot Step Double	30	₹ 1,500.00	
16	Oxygen Trolley Big - 250 CFT Cylinder	12	₹ 1,000.00	
17	Oxygen Trolley Big - 40 CFT Cylinder	30	₹ 1,500.00	
18	Patient Stretcher Trolley	12	₹ 3,000.00	
19	Drug Trolley Big with S.S Top	15	₹ 5,000.00	
20	Over Bed Table	200	₹ 50,000/-	
21	Dressing Trolley	15	₹ 3000.00	
22	Medicine Trolley	15	₹ 2500.00	
23	IV Stand	70	₹ 3500.00	

Sign of bidder

Re-Tender Enquiry. No.24/Furniture/213/2017-RISH(ADMN)

24	Ward Screen Stainless Steel with Curtain	30	₹ 3500.00
25	Platform/Footstep (Single Step)	100	₹ 2500.00
26	Platform/Footstep (Double Step)	50	₹ 2500.00

Sign of bidder

Chapter III
Specifications and allied Technical Details

Parameters and Technical Specifications for Executing the Work:

1. The participant: manufacture/companies having own manufacturing units or their authorized dealer can only participate. Proof of manufacturing is to be attached. Client may also visit and inspect the manufacture set up as deemed fit.
2. Technical committee shall inspect the samples before opening of financial bid on following parameters: -
 - (a) Fit & Finish
 - (b) Ease in assemble
 - (c) Durability
 - (d) Fit for application
 - (e) Knock down assembly.
3. In case Dealer is submitting the quote, Dealer has to get the authorisation manufactures firm for participating the tender.
4. Company /manufacturer/firm must have warehouse in the city or within Uttarakhand. (Enclosed Address details) The company/ manufacturer should be maintaining their office/warehouse in the city /state since last 5 years. Copy of shop and establishment act registration certificate to be enclosed for giving proof of establishment.
5. Manufacturer should be ISO 9001:2008/ ISO 14001:2004/ OHSAS 18001:2007 certified. Dealers participating should enclose certificate from their parent manufacturer company.
6. Manufacturer shall have in house quality assurance lab in which quality tests shall be tested on regular basis as per IS/ASTM standards.
7. The firm should be registered and should have the turnover of Rs. 25,00,000/- (Rupees twenty-five lakh only) for the last three consecutive years.
8. The firm has to submit a proof of turnover as mentioned above supported by documentary materials.
9. The delivery of the items will have to be made at AIIMS, Rishikesh. No transportation/ cartridge charges will be provided for the same.
10. The rate quoted should be firm and final and written in ink or typed against each item and should in no case be overwritten.

Administrative Officer,
AIIMS, Rishikesh.

Sign of bidder

Chapter – IV Contract Form

TENDER FORM – 1 – TECHNICAL INFORMATION AND UNDERTAKING.
(Tenderer may use separate sheet wherever required)

S.No.	Details of the Firm/Bidder	Page No.	Yes/No
1.	Name & Address of the Tenderer/ Concern		
2.	State clearly whether it is Sole proprietor or Partnership Firm or a Company or a Government Department or a Public Sector Organisation		
3.	Name and address of service centre nearby Rishikesh		
4.	Whether Bidders have quoted for each and every item mentioned in Chapter V (Yes/No).		
5.	List of Major Customer may be given on a separate sheet and proof of satisfactory supply, if any		
6.	Proof of the last three year's turnover of the firm which should not be less than Rs. 25,00,000/-(Rupees twenty five lakh Only) continuously for the preceding three years duly attested by a CA.		
7.	Permanent Account Number		
8.	VAT/Service Tax Registration Number/TIN No. with Proof		
9.	Whether copies of authenticated balance sheet by a CA for the past three years enclosed		
10.	Have you previously supplied these items to any government/reputed private organization? If yes, attach the relevant proof. Please provide a notarised affidavit on Indian Non Judicial stamp paper of Rs. 10/- that you have not quoted the price higher than previously supplied to any government Institute/Organisation/reputed Private Organisation or DGS&D rate in recent past. If you don't fulfil this criteria, your tender will be out rightly rejected.		
11.	Acceptance of terms & conditions attached (Yes/No). Please sign each page of terms and conditions as token of acceptance and submit as part of tender document with technical bid. Otherwise your tender will be rejected.		
12.	Any other information important in the opinion of the tenderer		
13.	Please submit a notarised affidavit on Indian Non Judicial stamp paper of Rs. 10/- that no case is pending with the Police against the Proprietor/firm/partner or the Company (Agency). Indicate any convictions in the past against the Company/firm/partner. Please also declare that proprietor/firm has never been black listed by any organization.		

Sign of bidder

Re-Tender Enquiry. No.24/Furniture/213/2017-RISH(ADMN)

S.No.	Details of the Firm/Bidder	Page No.	Yes/No
14.	Details of the Demand Draft/FD/TD/CD of bid Security (EMD) DD/FD/TD/CD No. Date Payable at		Details of cost of Tender fee Rs. 1145/- (if downloaded from website) DD No. Date Payable at

Note:

(i) In case of non-fulfilment of any of the above information/ document(s), the Tender will be summarily rejected without giving any notice.

(ii) Page number/serial number may be given to each and every page of Tender Documents and photocopies of the documents attached. Mention Page number, wherever the copy (ies) of the document(s) is kept.

(Dated Signature of the Tenderer with stamp of firm)

Date:

Place:

Undertaking

1. That I/we have carefully studied all the terms & conditions of NIT and shall abide by it.
2. That I/We shall supply the items of requisite quality.
3. That I/We undertake that the information given in this tender are true and correct in all respect and I/We hold the responsibility for the same.

(Dated Signature of the Tenderer with stamp of firm)

Date:

Place:

Sign of bidder

Chapter-V-
Format for Financial Bid

(To be submitted on the letterhead of the company / firm)

Sr. No	Name of Item	Quantity required	Unit rate inclusive VAT/Taxes and other expenses
1	2	3	4
1	Crash Cart	10	
2	Bed Side Locker	188	
3	Bed Side Screen (Ward Screen) Stainless Steel with single curtain, three section	80	
4	Fowler Bed, four section with mattresses	200	
5	Dressing Trolley	15	
6	Over bed trolley (Food Trolley)	200	
7	Stainless Steel Operation Instruments Trolley (Without Bucket Ring)	15	
8	Medicine Trolley	25	
9	Patient Examination Couch	8	
10	Examination Couch (Low Height)	4	
11	Stool SS, Round & Revolving top, Adjustable for heights	200	
12	Solid Linen Trolley	25	
13	Wheel Chair (SS)	15	
14	Single Foot Step	30	
15	Foot Step Double	30	
16	Oxygen Trolley Big - 250 CFT Cylinder	12	
17	Oxygen Trolley Big - 40 CFT Cylinder	30	
18	Patient Stretcher Trolley	12	
19	Drug Trolley Big with S.S Top	15	
20	Over Bed Table	200	
21	Dressing Trolley	15	
22	Medicine Trolley	15	
23	IV Stand	70	
24	Ward Screen Stainless Steel with Curtain	30	
25	Platform/Footstep (Single Step)	100	
26	Platform/Footstep (Double Step)	50	

1. L1 will be decided on the basis of unit cost.
2. I/We have gone through the terms & conditions as stipulated in the tender enquiry document and confirm to accept and abide the same.
3. No other charges would be payable by the Institute.

Sign of bidder

Place:

Signature of Bidder

Name

Business Address

Date:

Seal of the Bidder

Sign of bidder

BANK GUARANTEE FORM FOR PERFORMANCE SECURITY/ CMC SECURITY

To

Administrative Officer

All India Institute of Medical Sciences
Rishikesh,
Virbhadr Marg,
Rishikesh-249201

WHEREAS _____ (Name and address of the supplier) (Hereinafter called "the supplier") has undertaken, in pursuance of contract no _____ dated _____ to supply (description of goods and services) (herein after called "the contract"). AND WHEREAS it has been stipulated by you in the said contract that the supplier shall furnish you with a bank guarantee by a scheduled commercial bank recognised by you for the sum specified therein as security for compliance with its obligations in accordance with the contract; AND WHEREAS we have agreed to give the supplier such a irrevocable bank guarantee;

NOW THEREFORE we hereby affirm that we are guarantors and responsible to you, on behalf of the supplier, up to a total of. _____ (Amount of the guarantee in words and figures), and we undertake to pay you, upon your first written demand declaring the supplier to be in default under the contract and without cavil or argument, any sum or sums within the limits of (amount of guarantee) as aforesaid, without your needing to prove or to show grounds or reasons for your demand or the sum specified therein.

We hereby waive the necessity of your demanding the said debt from the supplier before presenting us with the demand.

We further agree that no change or addition to or other modification of the terms of the contract to be performed there under or of any of the contract documents which may be made between you and the supplier shall in any way release us from any liability under this guarantee and we hereby waive notice of any such change, addition or modification.

This guarantee will not be changed due to change in the constitution of the Bank or the supplier.

This guarantee shall be valid up to ____ months from the date of satisfactory installation of the equipment i.e. up to ----- (indicate date).

.....
(Signature with date of the authorized officer of the Bank)

.....
Name and designation of the officer

.....
Seal, name & address of the Bank and address of the Branch

Sign of bidder

Technical Specification

1. Crash Cart

- Emergency cart constructed of steel/aluminum and high density resin with epoxy paint.
- Defibrillator shelf with monitor straps, glove dispenser, sharp container, oxygen cylinder, cradle, IV pole, cardiac chest board, writing surface.
- Clear plastic overlay for top caps. ABS plastic overlay.
- Push handle built in the end panel for smooth and stable movement.
- Cart should be light, sturdy and scratch resistant.
- All drawers should be lockable individually.
- Should have minimum of five drawers with adjustable divider/Fixed dividers.
- Should have side bin discarding syringes and gloves.
- Castor should not be less than 5” diameter to facilitate quite an easy maneuverability, dust-prevention, flexible transportation.
- Size should be: - height: 100 to 110 cm.
- Base should not be less than 60 to 70 cm.
- Width and depth should be good enough to accommodate the necessary items.
- US/FDA/CE certified /ISO/BIS certified.
- Comprehensive warranty period 5 years after satisfactory installation.

2. Bed Side Locker

- Size (16 L x 16 W x 32 H) Frame work :- Mild Steel, 18-20 gauges , Epoxy Powder Coated antirust type, with minimum thickness at least 60 micron.
- Stainless steel top of bed side locker Made with stainless steel sheet of with thickness 18 gauge, 304 qualities.
- Top with three sides raise edges (Top edge if the raised edges should be bent and pressed to 180 degree to prevent sharp edge) one storage compartment and one drawer.
- The outside diameter of the legs of the locker should be 35-40 mm and thickness of 1.20-1.50 mm.
- One small drawer under the top of bed side locker to keep small things for the user and storage compartment on the lower side of the unit, with the door.
- Shoes made from hard rubber of uniform texture and chemically inactive to the action of mild acids.
- The manufacture should be ISO certified/or the product should be ISI marked.

Sign of bidder

3. Bedside Screen (Ward Screen) Stainless Steel with Single Curtain, three section.

- Overall size: 1675-1680 mmH X 2440-2450 mm W. Middle section width of 1210-1220 mm W and sides of width 610 mm W.
- Middle section should be constructed in two pieces and joined together at the middle.
- Two Nos. bases should be double bent and welded to the main frame.
- Two side sections should be hinged with middle section one on each side.
- Middle section should be fitted with four 5 cmdia. swiveling/rolling castors, and both sides should be fitted with one 5 cmdia. swiveling/rolling castor each.
- Hooks should be welded to middle section as well as on both side sections at top and bottom and spring wire should be fixed on hooks to receive screens.
- The material used should be ERW steel tubes of 19.05 mm OD X 1.22 mm thickness with 2 Nos. base of 25-30 mm OD x 1.22 mm thickness.
- All components should be thoroughly pre-treated chemically in eight tank pre-treatment system. The treated metal surface should then be coated with Epoxy Polyester Powder with paint film thickness of 50 microns or more and oven baked at 180 degree to 200 degree centigrade.
- Accessory: Curtain Cloth for Bedside Screen.
- The material of the curtains should be green in colour, opaque, light in weight, shrink resistant/preshrink, durable and suitable for frequent laundering.
- The manufacturer should be ISO certified /or the product should be ISI marked.

4. Fowler Bed, Four sections with mattress

- Dimension: 2090-2100mm L x 915-920mm W x 600-610mm H. with bed frame approx. Size: 1980- 2000mm L x 910-920mm W.
- The main frame should be made from 6cms x 3cms x 16 G M.S. ERW rectangular tubes.
- Four sections top should be made from 18 G C.R.C. sheets uniformly perforated and should be suitably fitted to the main frame.
- Back-rest and knee rest should be maneuverer by the screw mechanism, welded with approx. 30- 36 mm dia x16 G ERW M. S. Tube for linear movement in a approx. 32-38mm dia x 16 GERW M. S. covers.
- Tube which can be smoothly operated on thrust bearings.
- Two detachable handle shall be provided chrome plated with PVC grip.
- Detachable Head and Leg Bows: Should be made from stainlesssteel 30-34 mm dia x 18G tube with laminated panels of approx. size 810-820mm L x 140-150 mm wide x14-16 mm thick on stainless steel bracket.
- The base frame should be fitted with non-rusting swivel castor wheels 125-130 mm diameter, 2 with brake, 2 without brakes, cross legs.
- The bows should be bolted to the frame on brackets welded to the bows in such a way that bolt or nut should not appear on top surface of the bed frame.

Sign of bidder

Re-Tender Enquiry. No.24/Furniture/213/2017-RISH(ADMN)

- One Telescopic SS IV Rods. Moulded chart holder. Both sides of the bed should be provided with stainless steel detachable and collapsible full length railing made of minimum 25-35 mm dia x 18 gauge thick S.S. tubes housed in MS tubular frames.
- This should be remained in raised position with trigger type spring lock fixed on the tube. When in collapsible position, railing should be below the mattress level. Provision to fit Type B oxygen cylinder.
- A mattress thickness 100mm minimum suitable for the bed made thick PU foam 40 density suitable mattress covered with good quality Rexine.
- Provision of MS/SS two hooks to attach bags.
- Bed head panel with O2 outlet-1 no & High pressure flexible tube 3mtr & provision for one side fit in oxygen flow meter, one side fit in O2 outlet.(for 10 % of bed).
- Epoxy Polyester Powder not less than 60 micron with eight tank pre-treatment system.
- The manufacturer should be ISO certified /or the product should be ISI marked.

5. Dressing Trolley

- Framework Complete made up stainless steel 16-18 gauge, 304 qualities. Tubular/ square frame work with diameter 25-35mm.
- Two SS shelves over with SS Railing on all four sides.
- The trolley fitted with SS bucket & SS Bowl.
- The trolley mounted on 100-125 mm diameter castors with brakes cross wheel.
- Approx. size-36"x18"x32".
- Two drawers made of SS below upper shelves.
- The manufacturer should be ISO certified /or the product should be ISI marked.

6. Over bed Table /Food trolley

- Should have height adjustable facility from 850mm to 1100mm with the help of operating lever which activates the gas spring to assist the table top to fit.
- Gas spring should function smoothly with adjustable height and consistent motion during operation.
- Table top frame shall be designed to hold the top as well as extension work as a handle for the handling of over bed table.
- Should have anti scratch, good surface finish ABS laminated top having dimension 740-780 mm Lx 440-480 mm W approximately.
- Should be mounted on four 5cm swivel castor with brakes.
- All MS parts are 8 tank pre-treated and powder coated.
- The manufacturer should be ISO certified /or the product should be ISI marked.

Sign of bidder

7. Stainless steel operation instruments trolley (without bucket ring)

- The main dimension of trolley should be 650-700mm L x 450-475 mm W x 850-900 mm H.
- Frame work of welded steel tubular/square construction. The trolley should be provided with 2 stainless steel shelves.
- The shelves edges should be bent & pressed to 180 degree to prevent sharp edge.
- All welded joints should be sound, clean & well formed. The vertical members should be perpendicular to horizontal members. All the surfaces should be smooth & free from pitting.
- Castors: -The castors should be of 10 cm diameters with rolling cum swiveling movement. The wheels should be provided with dust covers & the wheels should be well secured with the help of bolt and nuts.
- The material used should be as follows :-The thickness of tubes used & their corresponding outside diameter for different parts are as under :-
- Vertical Members: -Thickness of tube should be 1.20-1.30 mm & outside diameter of tube should be 25 – 30 mm of stainless steel tube.
- Horizontal Members: - Thickness of tube should be of 1.20-1.30 mm & outside diameter of tube should be of 19-20 mm of stainless steel tube.
- Top: Stainless steel sheet thickness is not less than 0.8 mm at any point.
- Railing should be of 10 mm dia S.S. shafting.
- The manufacturer should be ISO certified /or the product should be ISI marked.

8. Medicine Trolley

- Frame work made from SS steel material.
- Flat top of SS and at least 6 inch deep removable bucket at bottom.
- Should have multiple long drawers to hold drug strips made of high quality epoxy plastic or steel material with convenient and smooth slide in and slide out motion (At least 28-32 separate drawers in about six to eight row).
- The front of the each drawer should be half covered on which removable medicine label can be pasted and upper half open to see content inside.
- Dimension: approx. Size 750-760(L) x 440- 450(W) x 840-850(H) mm.
- All stainless steel should 304grade/ 16 gauges.
- Equipped with Waste bin, needle disposable container, file cassette & guard rails.
- Equipped with lock key system.
- Swivel noiseless caster with brakes 10 cm diameter.
- The manufacturer should be ISO certified /or the product should be ISI marked.

9. Patient Examination Table

- Dimension: approx. size: 1890-1950 mm L x 560-600mm W x 840-900mm H. Fixed upholstered top 64mm thick in two sections.
- Body frame work made from 18G. CRCA sheet and 20 mm x 40mm x 18 G MS.
- Rectangular Tubes Couch fitted with stainless steel Legs.

Sign of bidder

Re-Tender Enquiry. No.24/Furniture/213/2017-RISH(ADMN)

- Headrest adjustable on gas spring.
- Upper section of box approx. size 1220 mm L x 460 mm W x 630 mm H with three sliding drawers of approx. size 320 mm L x 430 mm W x 75 mm H.
- Lower section comprises of three cabinets of approx. inside size 350 mm L x 440 mm W x 430 mm H with separate doors & lock. B.P. apparatus tray made of 18 G MS sheet of approx. size 350 mm L x 120 mm W x 20 mm H provided on a winging rod rotating through a bush welded on the body of the couch.
- Should have Sliding Inbuilt Step Stool. All mild steel components should be thoughly pre-treated chemically to remove rust and foreign matter like Grease, Oil etc. by dip tank process pre-treatment system.
- The treated Metal Surface should have coating of Epoxy Polyester Powder and oven baked at 180 degree to 200 degree Centigrade to avoid contamination of the clean metal surface from dust particles (thickness not less than 60 micron).
- The manufacturer should be ISO certified /or the product should be ISI marked.

10. Examination Couch (Low Height)

- Over all dimension 1890 mm L x 560 mm W x 650 mm H.
- All other specification same as standard height couch.

11. Stool SS, Round & Revolving top, adjustable for heights

- This is only a representative/indicative picture. It does not exactly meet the specifications mentioned below.
- Tubular three legged SS base with Legs fitted with thick high quality nylon grommets.
- Stainless Steel polished top with diameter not less than 30cm.
- Height adjustable by rotating SS Top from approx. 48cm to 65cm.
- All the Stainless Steel should be seamless conforming to 304 grade/ 16 gauge and polished finished.
- The manufacturer should be ISO certified /or the product should be ISI marked.

12. Solid Linen Trolley

- Overall approx. size: 900-930mm H x 500-520mm dia. SS tubular framework fitted with three swivel castors, 100mm dia.
- Framework made of 25-30mm dia x 18G verticals, upper ring made of 19mm dia x 18G tube and support stays of 15-17mm dia. X 18G stainless steel tubes. Supplied with canvas bag.
- All SS components should be of 304 qualities.
- The manufacturer should be ISO certified /or the product should be ISI marked.

Sign of bidder

13. Wheel Chair (SS)

- Dimensions: - Width - 660-665 mm Depth - 1075-1100 mm Height- 935-950 mm.
- Seat and Back:- Seat size 450 mm X 450 mm X 50 mm thick and back size 450mm X 250mm X 25 mm thick Rubber foam seat ISI marked 1741-1960 with groove, or P.U. foam of same size and thickness of 32 density should be provided with Rexine Polynoval/ National.
- Thickness of Rexine 0.6-0.7 mm or above should be provided on 12mm thick ply and back seat should be fixed with 2 Nos. M.S. Flat 25 X 5mm thick to be welded with ERW pipe for giving support on back side of seat as a secured.
- Arms: - Two numbers arms duly polished shall be made from seasoned hard hillock wood/Shisham/Babool and fixed to the tubular arm securely with screw which should not be projected out or injected molded from black polypropylene which should be fixed securely with screws.
- Wheels: - Two numbers plug type swivel castor zinc plated wheel size: 100X32mm (4"X1 1/4") having load capacity 75 kg each should fitted with bottom end of the up-right should be welded with additional outer pipe to hold the caster firmly.
- Wheel shall be made of semi round rubber hardness 85-90, pressed fitted over the virgin polyamide pulley. The wheel shall have two number ball bearing/single roller bearing along with sleeve and 3/8" nut and bolt.
- Cap of 20SWG (Plastic) should be provided on both sides to prevent dust. The pressed steel double thrust ball bearing type form should be 12SWG (minimum) mild steel sheet.
- The length of 32-35mm dia mild steel plug should be approximately 50 mm including collar. It should have 1/4" hole for side set screw.
- Cycle Rim :- Tow number bicycle rim with axle and hub size 26" X 1 1/2", with 40 Nos spoke with sold rubber tire should be provided on rim and M.S. flat 25 X 6 mm thick to be provided to support the axle rime as a safe guard.
- Both Side of wheel chair self-propelling chrome plated, hand hoops two handle with proper hand grip should be provided.
- Frame:-Framework of ERW pipe 25-27mm X 1-2 mm thick and 19 mm X 1-2 mm thick ERW pipe for crossing. Side panel of 1-2 mm CRCA Sheet should be used.
- Foot Rest: - Two numbers folding aluminum casting footrest should be provided 125mm above the floor level.
- Welding: - The mild steel welding should be done by the MIG welding.
- Finishing: - All steel components should be thoroughly pre-treated chemically in 6-8tank system. The treated metal surface should be powder-coated paint. The thickness of paint not less than 60 microns and oven baked paint.
- Color: - T.A. Grey/Cream Color.
- The manufacturer should be ISO certified /or the product should be ISI marked.

Re-Tender Enquiry. No.24/Furniture/213/2017-RISH(ADMN)

- The monitor should have:- High resolution colour TFT display of minimum screen size >6”.
- Should be able to monitor ECG,NIBP, 2 IBP, SpO2. Temperature and Respiration.
- Plethysmograph with monitor at least three channel.
- 24 Hrs. graphical/ tabular trends.
- NIBP trends memory should be at least 50 readings (tabular)
- Should display Critical Alarm summary.
- Suitable for Adult / pediatric.
- Selectable Arrhythmia detection.
- Should have option to attach inbuilt two channel recorder.
- Must have Graded and Colour coded alarms.
- User selectable screen formats and user- friendly menu driven functions through optical encoder.
- Battery backup for at least 1 Hrs.
- It should be European CE/USFDA Certified.
- Should be supplied with one 3 lead ECG cable, Reusable SpO2 sensor, NIBP cuffs (each for Adult and child) IBP cable.

14. Single Foot Step

- MS tubular legs fitted with high quality nylon grommets.
- MS made top with high grade 3mm nylon matting and aluminium beading.
- Overall size: - 460(L)*250(W)*230(H).
- Epoxy coated.

15. Foot Step Double

- MS tubular legs fitted with high quality nylon grommets.
- MS made top having high grade 3mm nylon matting and aluminium beading.
- Overall size: - 460(L)*510(W)*460(H)(for Double Foot Step Stool)
- Epoxy coated.

16. Oxygen Trolley Big- 250 CFT Cylinder

- Frame of the cylinder trolley should be with hi-grade MS tubular steel.
- Framework of the cylinder trolley should be mounted on two 10cm wheels.
- Epoxy powder coated.
- For big (250cft) Oxygen Cylinder.
- Mounted on 100 / 150 mm diameter castor for mobility.

17. Oxygen Trolley Small- 40 CFT Cylinder

- Frame of the cylinder trolley should be with hi-grade MS tubular steel.
- Framework of the cylinder trolley mounted on two 10cm wheels.
- Epoxy powder coated.
- For small (40cft) Oxygen Cylinder.
- Should be mounted on 100 / 150 mm diameter castor for mobility.

Sign of bidder

18. Patient Stretcher Trolley

- Overall Size: 1905mm L x 710mm W x 660mm To 910 mm H.
- Stretcher dimension 1830 mm L x 555 mm W.
- Two section top. Height adjusted by foot operated maintenance free hydraulic pump.
- Height adjustment shall be obtained by hydraulically operated mono block type linear actuator pump foot operated actuation having stroke of 140 +/- 5 mm, push force 10 KN at 270 bars, number of complete pump stroke 22 to 24 for full stroke length.
- X-ray permeable removable stretcher, Backrest raised on ratchet. Quick Trendelenburg as well as reverse Trendelenburg positions shall be provided with easily accessible operating handle provided with two gas springs for easy action.
- S.S. saline rod with 12 mm dia S.S. rod shall telescope in SS socket tube approx. 15.8 mm dia x 18G welded on angular base bracket of 14G SS sheet.
- Nylon bracket provided to prevent colour damage. It could be placed at four different locations. Complete with sliding X-ray cassette holder, storage tray.
- Trolley shall be mounted on 125 mm dia non-rusting imported castor wheels two with brakes and two without. Castor housing and wheels made from high grade non floor-staining synthetic materials with integrated thread guards.
- Wheel centre having precision ball bearing to run smoothly. Complete with corner buffers, one on each corner. Covered handles. Oxygen cylinder arrangement.
- It shall have a pair of Stainless steel tuck down type railings made of 19 mm dia x 18G tube fitted with M.S. brackets.
- Effective railing height above main frame is approx. 235 mm & length of the railing is 1175 mm.
- All MS parts and 8 tank Pre-treated & powder coated & SS parts finished with Matt polish.
- Mattress should be provided with a size 2 inch thickness PU foam which can be fixed to the trolley by Valero similar mechanism.

19. Drug Trolley Big with S.S Top

- Overall approximate size: W 490 mm x D 580 mm x H 1040 mm.
- Main frame should be made up of CRCA rectangular 50mm X 25mm X 18 g and 25 mm X 25 mm X 18 g.
- The Trolley should have 3 no's tray for keeping medicine.
- The Top tray should be made up of 304 grade stainless steel sheet of 20 G and remaining 2 no's should be made up of CRCA sheet of 20 gauge.
- It should be mounted of 100 mm dia non rusting swivelling castors with brakes four no's corner buffer.
- It should be fitted with S.S. handle with hand grip.

Re-Tender Enquiry. No.24/Furniture/213/2017-RISH(ADMN)

- Finish: All components should be pre-treated in separate eight tank process for better finish, good adhesion and corrosion protection. Process includes Hot Degreasing, Derusting, Activation, Phosphating & No's of water rinses as per IS 3618-1966 class 'C' type and then pre-treated material is coated with epoxy powder with film thickness of 60 microns (approx..) and then oven baked at 180 to 200 degree centigrade.
- Alternate breaks in wheels.

20. Over Bed Table

- Size: Top 810mm L x 352mm W .
- Laminated top should be fitted on mild steel square tubular telescopic stem with geared.
- Handle for height adjustment from approx. 760mm to 1050mm. Base frame should be of mild steel rectangular tubular base frame mounted on four castors of 50mm dia.
- All mild steel components should be thoroughly pre-treated chemically to remove rust and foreign matter like Grease, Oil etc. by dip tank process pre-treatment system.
- The treated Metal Surface should have coating of Epoxy Polyester Powder and oven baked at 180 degree to 200 degree Centigrade to avoid contamination of the clean metal surface from dust particles.

21. Dressing Trolley

- Complete made up stainless steel.
- Two SS shelves over with SS Railing on all four sides.
- The trolley fitted with SS bucket & SS Bowl.
- The trolley mounted on 100 mm diameter castors.
- Finish- Pre-treated & Epoxy powder coated. Approx. size-36"x18"x32"
- Four wheels with locking and unlocking system should be available.
- Tubular frame work.
- Two drawers made of SS below upper shelves.
- Shelves should be of SS 304 Grade steel. So that is should not rust and last for years.

22. Medicine Trolley

- Frame work made from SS steel material.
- Flat top of SS and at least 6 inch deep removable bucket at bottom.
- Should have multiple long drawers to hold drug strips made of high quality epoxy plastic or steel material with convenient and smooth slide in and slide out motion (At least 28- 32 separate drawers in about six to eight row)
- The front of the each drawer should be half covered on which removable medicine label can be pasted and upper half open to see content inside.

Sign of bidder

Re-Tender Enquiry. No.24/Furniture/213/2017-RISH(ADMN)

- Approx size 750(L) x 450(W) x850(H) mm.

23. IV Stand

- Overall approx. size: height: - 136 to 244 cm (with adjustable height by turnknob).
- Main Frame: Strong & Sturdy five legged neatly made base from stainless steel mounted on five 2.5cm diameter swivelling ball castors of good quality.
- Stainless Steel four hocked I.V. rod.

24. Ward Screen Stainless Steel with Curtain

- Overall approx size: 1680mm H x 2450mm W.
- MS tubular construction in there sections made of 19mmx 18G. Mild steel round tube.
- Frame mounted on 25.4mmx18G mild steel round tubular base.
- Middle span 1210mm wide mounted on four swivel castors, 50mm dia. Side spans 610mm wide each rotating on the Swivel castors, 50mm dia. Supplied with hooks & springs with curtain cloth.
- All mild steel components should be thoroughly pre-treated chemically to remove rust and foreign matter like Grease, Oil etc. by dip tank process pretreatment system.
- The treated Metal Surface should have coating of Epoxy Polyester Powder and oven baked at 180 degree to 200 degree Centigrade to avoid contamination of the clean metal surface from dust Particles.

25. Plat form /footsteps (single step)

- Overall step size approx. 505mm L x 305mm W. First step height 230mm approx.
- Step made of 18G CRCA sheet. Welded on MS. Tubular frame of 25.4mm x 18G fitted with aluminum tread flats of size: 500mm L x 32mm W x 3.4 mm thick, fitted by aluminum pop rivet. Legs fitted with PVC.Shoe with nylon reinforcement.
- All mild steel components should be thoroughly in-house pre-treated chemically to remove rust, grease, oil, etc. by dip tank processes, including separate degreasing, pickling, phosphating each followed by

Sign of bidder

Re-Tender Enquiry. No.24/Furniture/213/2017-RISH(ADMN)

water rinsing passivating and hot air drying to give phosphate coating.

- The treated metal surface should then be coated inhouse with epoxy polyester powderwith paint film thickness of 50 microns (minimum) and oven baked at 180 deg. to 200 deg. Centigrade.

26. Platform /foot step (double step)

- Overall Step size approx. 505mm L x 305mm W. First step height 230 mm approx. & second step size 450 mm approx. Step made of 18G CRCA sheet.
- Welded on MS. tubular frame of 25.4mm x 18G fitted with aluminum tread flats of size: 500 mm L x 32 mm W x 3.4 mm thick, fitted by aluminum pop rivet. Legs fitted with PVC. Shoe with nylon reinforcement.
- All mild steel components should be thoroughly pre-treated chemically to remove rust and foreign matter like Grease, Oil etc. by diptank process pretreatment system.
- The treated Metal Surface should have coating of Epoxy Polyester Powder and ovenbaked at 180 degree to 200 degree Centigrade to avoid contamination of the clean metal surface from dust particles.

Sign of bidder